

In the claims:

1. (currently amended) A modified pin assembly ~~in~~ in a common cylinder lock, said cylinder lock having a body and cylinder plug containing a plurality of standard pin assemblies, each of said plurality of standard pin assemblies being disposed in a pin chamber, wherein each crosses a shear line, and is linearly displaceable along said pin chamber, each standard pin assembly comprising a tumbler pin, a driver pin and a biasing spring, arranged so as to define a locked cylinder position, in which said driver pin extends beyond the shear line, preventing rotation of the cylinder plug, said tumbler pin being positioned opposite said driver pin, within said pin chamber,

wherein said modified ~~at least one~~ pin assembly, ~~modified to prevent~~ prevents impact-driven manipulation of said ~~locks~~ lock, said ~~at least one~~ modified pin assembly comprising:

a modified pin set comprising a tumbler pin and driver pin, said modified pin set being provided with motion alteration means adapted so as to alter the magnitude of its response to an impact-driven blow applied to said tumbler pin, relative to the magnitude of the response of the standard pin assemblies contained in said common cylinder lock,

such that when said tumbler pin is linearly displaced in response to an impact-driven blow of a given intensity, a portion of said impact-driven blow intensity is transmitted to said driver pin, causing it to be linearly displaced, as well, under influence of said motion alteration means,

and while said standard pin assemblies clear the shear line, said driver pin of said modified pin set continues to block the shear line,

consequently preventing unauthorized manipulation of said cylinder lock.

2. (withdrawn)

3. (currently amended) The modified pin assembly of claim 1 wherein said motion alteration means of said modified pin assembly, ~~containing a tumbler pin and a driver pin, is adapted so as to alter linear displacement thereof, by forming~~ comprises a recession formed in one of said pins contained in said pin assembly, and ~~an engagement means~~ a protrusion, in the other of said pins, for engaging said recession, such that when an impact-driven blow of a given intensity is applied so as to linearly displace said tumbler and driver pins, said pin ~~engagement means~~ protrusion engages said pin recession, strongly binding the tumbler and driver pins together.

4. (withdrawn)

5. (withdrawn)

6. (withdrawn)

7. (withdrawn)

8. (withdrawn)

9. (original) The modified pin assembly of claim 3 wherein means are provided to enable release of said engaged tumbler and driver pins.

10. (original) The modified pin assembly of claim 9 wherein said unauthorized manipulation is represented

by said engaged tumbler and driver pins and said release of said engaged tumbler and driver pins indicates an attempted unauthorized manipulation.

11. (currently amended) A method for preventing unauthorized manipulation of a common cylinder ~~locks~~ lock, ~~wherein~~ said common cylinder ~~locks~~ lock having a body and a cylinder plug containing ~~are comprised of~~ a plurality of standard pin assemblies, each of said plurality of standard pin assemblies being disposed in a pin chamber, wherein each crosses a shear line, and is linearly displaceable along said pin chamber, each standard pin assembly comprising a tumbler pin, a driver pin and a biasing spring, arranged so as to define a locked cylinder position, in which said driver pin extends beyond the shear line, preventing rotation of the cylinder plug, said tumbler pin being positioned opposite said driver pin, within said pin chamber,

said method comprising:

providing ~~at least one~~ a modified pin assembly in said common cylinder lock, ~~modified~~ to prevent impact-driven manipulation of ~~said locks~~ thereof, said ~~at least one~~ modified pin assembly comprising:

a modified pin set comprising a tumbler pin and driver pin, said modified pin set being provided with motion alteration means adapted so as to alter the magnitude of its response to an impact-driven blow applied to said tumbler pin, relative to the magnitude of the response of the standard pin assemblies contained in said common cylinder lock,

such that when said tumbler pin is linearly displaced in response to an impact-driven blow of a given intensity, a portion of said impact-driven blow

intensity is transmitted to said driver pin, causing it to be linearly displaced, as well, under influence of said motion alteration means,

and while said standard pin assemblies clear the shear line, said driver pin of said modified pin set continues to block the shear line,

consequently, preventing unauthorized manipulation of said cylinder lock.

12. (withdrawn)

13. (currently amended) The method of claim 11 wherein said motion alteration means of said modified pin assembly, ~~containing a tumbler pin and a driver pin,~~ ~~is adapted so as to alter linear displacement thereof,~~ by forming comprises a recession formed in one of said pins contained in said pin assembly, and ~~an engagement means~~ a protrusion, in the other of said pins, for engaging said recession, such that when an impact-driven blow of a given intensity is applied so as to linearly displace said tumbler and driver pins, said pin ~~engagement means~~ protrusion engages said pin recession, strongly binding the tumbler and driver pins together.

14. (withdrawn)

15. (withdrawn)

16. (withdrawn)

17. (withdrawn)

18. (withdrawn)

19. (original) The method of claim 13 wherein means are provided to enable release of said engaged tumbler and driver pins.

20. (original) The method of claim 19 wherein said unauthorized manipulation is represented by said engaged tumbler and driver pins and said release of said engaged tumbler and driver pins indicates an attempted unauthorized manipulation.

21. (new) A modified pin assembly in a common cylinder lock, said cylinder lock having a body and cylinder plug containing a plurality of standard pin assemblies, each of said plurality of standard pin assemblies being disposed in a pin chamber, wherein each crosses a shear line, and is linearly displaceable along said pin chamber, each standard pin assembly comprising a tumbler pin, a driver pin and a biasing spring, arranged so as to define a locked cylinder position, in which said driver pin extends beyond the shear line, preventing rotation of the cylinder plug, said tumbler pin being positioned opposite said driver pin, within said pin chamber,

wherein said modified pin assembly prevents impact-driven manipulation of said lock, said modified pin assembly comprising:

a modified pin set comprising a tumbler pin and driver pin, said modified pin set being provided with motion alteration means adapted so as to alter the magnitude of its response to an impact-driven blow applied to said tumbler pin, relative to the magnitude of the response of the standard pin assemblies contained in said common cylinder lock,

such that when said tumbler pin is linearly displaced in response to an impact-driven blow of a given intensity, a portion of said impact-driven blow intensity is transmitted to said driver pin, causing

it to be linearly displaced, as well, under influence of said motion alteration means,

and while said standard pin assemblies clear the shear line, said driver pin of said modified pin set continues to block the shear line,

consequently preventing unauthorized manipulation of said cylinder lock,

wherein said motion alteration means of said modified pin assembly comprises a recession formed in one of said pins contained in said pin assembly, and a protrusion, in the other of said pins, for engaging said recession, such that when an impact-driven blow of a given intensity is applied so as to linearly displace said tumbler and driver pins, said pin protrusion engages said pin recession, strongly binding the tumbler and driver pins together.